

HM-A400 Mobile Label Printer

- 1.2-meter drop proof
- Compatible with main delivery company APP
- Support to charge by power bank
- Built-in vector font makes printing more clearly
- Support to print through Wechat applets
- Paper width adjustable block to support more types of paper



Specification

Item	Parameter	
Printing	Printing Method	Direct line thermal printing
	Resolution	203dpi (8dots/mm)
	Printing Speed	Max. 80mm/s (receipts, 12.5% printing rate)
	Printing Width	Max. 104mm
Human-Computer Interface	Buzzer	Internal buzzer
	Button	POWER button, FEED button
	LCD Display	Dot matrix: 96x39
Communication Interface	Bluetooth	Dual-mode Bluetooth 4.0/BLE , support Applet and multi-link application
	USB	USB Type C
	Wi-Fi	802.11 b/g/n 2.4GHz
		Wireless Mode: Station/SoftAP/Station+SoftAP
Memory	RAM	32MB
	Flash	16MB
Software Function	Command Set	CPCL, ESC/POS
Character	Built-in font of English and Number	Standard CPCL built-in font (7 fonts, 25 font sizes)
	Chinese	Support Chinese vector GBK font
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code

Detection	Sensors	Gap sensor/Out-of-paper sensor/TPH temperature sensor/Cover open sensor,
Power	Adaptor	Input: AC 100-240V Output: DC 5V/2A
	Battery	Built-in rechargeable Li-ion battery, 7.4V, 2600mAh
Paper	Paper Type	Thermal receipt paper (with black mark), thermal label paper
	Paper Width	42~110mm
	Paper Thickness	0.06mm~0.20mm
	Roll Paper Diameter	Max. 50mm
Environmental Parameters	Paper Loading	Easy paper loading
	Operation Condition	0°C to 45°C, 10% to 85%RH
	Storage Condition	-20°C to 60°C, 10% to 90%RH
	IP Protection Level	IP42
Physical Parameters	Drop Test	1.2m
	Dimension (LxWxH)	144x105x58mm
	Weight	0.48kg
Reliability	TPH Life	50km

